



REVISION RECORD				
NO	CAR/DC	DESCRIPTION	APP'D	DATE
2		Create from R1	PES	10/09/08
3		WV/4 was DVM/2, JPI was open, PSI reversed	PES	07/01/10
3		J6-9 was MAINON, add J6-11	PES	07/16/10
3		PS1 was DIP, Q1 decal corrected	PES	08/12/13

U1A	M-B352	Fuse Clip, PCB, 1/4"
U1B	M-B352	Fuse Clip, PCB, 1/4"
U1C	M-B352	Fuse Clip, PCB, 1/4"
U1D	M-B352	Fuse Clip, PCB, 1/4"
U1E	M-B352	Fuse Clip, PCB, 1/4"
U1F	M-B352	Fuse Clip, PCB, 1/4"
U1G	M-B352	Fuse Clip, PCB, 1/4"
U1H	M-B352	Fuse Clip, PCB, 1/4"
U1I	M-B352	Fuse Clip, PCB, 1/4"
U1J	M-B352	Fuse Clip, PCB, 1/4"

Notes:
When Aux unit is connected, only 480 VAC mode is allowed
VRLY redesigned with DC-DC isolator

COMPANY: Electrical Test Instruments, Inc.			
TITLE: PI-2500 Control PCB w/VRLY For PCB M-C405 - R3			
DRAWN: PES	DATED: 10/09/08		
CHECKED:	DATED:		
QUALITY CONTROL:	DATED:		
RELEASED:	DATED:		
CODE:	SIZE:	DRAWING NO: S-B259	REV: 3
SCALE:			SHEET: OF